





# With your needs in mind.

Nowadays we live in a constant rush, trying to find peace, beauty, and a safe refuge at home and in the places where we live. A sense of security and harmony definitely improves everyday quality of life. INVADO understands and respects these needs. Being one of the most rapidly developing manufacturers of door joinery and skirting boards in Poland, we do our best to give you products that meet your needs, with high, individual aesthetics and the best possible functional features. INVADO is also a leading supplier of components for the furniture industry—its market position is being built on the basis of over thirty years of experience and continuous investment in technology, people and quality improvement.









# Quality above all

INVADO continually strives to ensure optimal quality of its products, taking into account our users' personal needs. Quality is paramount—it is the basic issue in the design phase and remains the common denominator for all production processes. ISO 9001 certificate provides such an approach to the issue of quality. All INVADO products meet European standards. The high level of products and services next to the price and delivery time is the Company's primary objective, ensuring its perception as a trusted partner.

# **INVADO Technology**

Production of door leaves and door frames is the strongest point of our INVADO offer, therefore the implementation of innovative production technology of foiled doors (INVADO Technology) became a major breakthrough in the Company's activity. The most distinct feature of this technology is foiling surfaces without connecting foil on rebate edges. Because of this method the edge of a door leaf looks aesthetically clean and is also more resistant to damage. It's very unlikely to break off the foil because it ends in the inner corner of the rebate—invisible to the eye. "Technology of foiling flat doors in the mass production system" is in use since 2007 when it comes to all foiled doors. In addition—off-rebate foiling makes the INVADO doors the only ones on the market to have rounded edges, safe for both adults and children's hands. Nowadays, thanks to the innovative method of doors' production, INVADO is among the most technologically advanced companies in Europe.

# Hygienic certificates

Certifications aim to prevent materials and products hazardous to health and life of its users to be introduced to the general use or limit the allowable scope and method of their application for the elimination of health risks. All INVADO products have hygienic certificates:

- interior door frames in natural veneer No. 48/322/49/2017
- interior door frames in artificial veneer No. 441/322/451/2017
- interior door leaves in natural veneer No. 46/322/47/2017
- interior door leaves in artificial veneer or flat lacquered No. 348/322/353/2020
- skirting boards in natural veneer No. 47/322/48/2017
- skirting boards in artificial veneer No. 256/322/261/2019

# Technical Approvals and National Technical Assessments:

Technical Approvals (until the end of their term) and National Technical Assessments, issued by Building Research Institute, are decisions to grant use of building materials and products. In accordance with the Construction Products Act of 16 April 2004, as amended (unified text: Journal of Laws of 2016, item 1570), the products to which the Technical Approvals and National Technical Assessments relate, may be placed on the market and can be used in construction. INVADO Company assessed and verified the constancy of performance, made a national declaration of performance and labeled the products with a construction mark in accordance with applicable regulations. INVADO's Technical Approvals and National Technical Assessments:

- Interior flat and glass doors—ITB-KOT-2017/0313 edition 1;
- Modular interior doors—ITB-KOT-2017/0003 edition 1;
- Folding, swinging and sliding interior doors—ITB-KOT-2018/0296 edition 1;
- Technical doors GUARDIA El30 and El60 (wooden interior entrance doors of HALSPAN system)—ITB-KOT-2018/0407 edition 1; National Certificate Of Stable Performance AC 158-UWB-W1355;
- Technical doors IGNIS—ITB-KOT-2018/0599 edition 1, National Certificate Of Stable Performance AC 158-UWB-W1337;
- Interior entrance doors EGIDA with increased resistance to breaking-in—ITB-KOT-2018/0598 edition 1;
- Adjustable door frames for interior doors—ITB-KOT-2019/1221 edition 1;
- Block door frames for interior doors OB3 type P—ITB-KOT-2017/0312 edition 1;
- Door frames SARA-PRO for interior doors—ITB-KOT-2019/1076 edition 1;
- Metal door frame—ITB-KOT-2021/2091 edition 1;
- Housing system for metal frames—ITB-KOT-2019/1221 edition 1.

# **CERTIFICATES AND AWARDS:**



# CERTIFICATE RESOURCES SAVED

INVADO has obtained the international certificate in waste management and recycling issued by INTERSEROH zero waste solutions.



## GOOD BRAND 2019 AND 2021

An independent group of experts has confirmed that the products signed with the INVADO logo can be described using such words as: quality, trust and reputation. These three guidelines decide which selected brands are among the renowed brands. We are proud and grateful for that and at the same time we would like to thank our Customers for trusting us by

choosing INVADO doors for your dream interiors, our Business Partners for the fruitful cooperation, recommendation, and support, and all our INVADO employees for building together a good brand at every stage of its creation.



# CONSUMER'S LAUREL

INVADO brand has been recognized by Polish consumers and honored with the prestigious Consumer's Laurel emblem



# voc

The VOC certification tests the emission of volatile organic compounds released from the facility and, depending on the results obtained, the tested sample is assigned a class, ranging from A+ (best) and C (worst). The possession of the VOC certificate confirms that the product

does not release harmful for health substances inside the house, such as formaldehyde and benzene, a carcinogenic elements that unfortunately are often contained in paints, and materials used on windows.



# ISO 9001

The INVADO Company applies to the Quality Management System and fulfills requirements of: PN-EN ISO 9001 in scope of: designing, production and sale of furniture components and finishing profiles, interior doors made of wood and woodbased materials and technical doors.



The mark of responsible forestry

Control of Product Origin and environmental protection are the leading elements of INVADO's development strategy. This is confirmed by an international certificate issued by the Forest Stewardship Council® and obtained by the company

Ask for FSC® certified products in our range.



WARRANTY ON INVADO DOORS















GOOD TO KNOW

6-7 AVAILABLE DECORS

**8-9** AVAILABLE **GLASS** 

9







# COLLECTION OF MODULAR DOORS

10-51







# 52-79

# COLLECTION OF FOILED DOORS























COLLECTION OF GLASS DOORS



**COLLECTION OF FOLDING DOORS** 



NORMA DECOR AND LIBRA 82

SLIDING SYSTEMS



POCKET DOOR SLIDING SYSTEM WALL-MOUNTED SLIDING SYSTEM

# **TECHNICAL DOORS**



INTERIOR ENTRANCE DOORS—EGIDA	88
FIRE DOORS— <b>IGNIS</b>	90
FIRE DOORS—GUARDIA	92

# **TECHNICAL INFORMATIONS**







BLOCK DOOR FRAME	95
ADJUSTABLE DOOR FRAME	96
ADJUSTABLE DOOR FRAME FOR NON-REBATED DOORS	97
METAL FRAMES	98
CONCEALED DOOR FRAME SARA-PRO	100
HOUSING SYSTEM FOR METAL FRAME	101
-	· · · · · · · · · · · · · · · · · · ·

# **ACCESSORIES**



MW	Excitations			o ratigion
	1	1	0	@ rations
hande SPIGOUA-02		-		•
A-C-		********	_	8 mm



102

# **FOILED AND MODULAR DOORS:**

# **FOILED DOORS**

Visually, **foiled doors** are lighter than modular ones, which is combined with their stability. Construction: frame made of MDF board or finger joint pinewood. Filling: "honeycomb" or tubular chipboard, which is charged extra. The frame with filling is covered with a 3 mm-thick HDF board from both sides and wrapped with a decorative foil. For installation of filling elements in these doors, the glazing bars of different profiles are used.

# RESISTANCE RESISTANCE 10 LOAD 2 or 3 (starting from width "90") screw-in pivot hinges "Honeycomb" (cardboard) OPTIONAL FILLING AT EXTRA CHARGE Tubular chipboard No Mide selection of HANDLES FOIL CONNECTION IN THE REBATE Immovative internology of folling


# **MODULAR DOORS**

Construction of **modular doors**: two vertical elements, upper and lower horizontal elements. Filling: MDF panels of different thickness or glass 4 mm-thick. For each model you can select a decorative foil. Glass and other filling elements in these door leaves are not installed using glazing bars, but with all the construction elements at once, which greatly improves their stability.



# FOILS—TYPES OF WOOD TEXTURE (GRAINING):

Structures of INVADO foils can be divided into 3 categories:



# UNIDIRECTIONAL FOIL WITH VERTICAL TEXTURE:

Most of INVADO foils is available in this type of texture. Exceptions: Chestnut (ENDURO), Italian oak and Severo oak (ENDURO 3D).



# UNIDIRECTIONAL FOIL WITH HORIZONTAL TEXTURE:

Currently in INVADO offer there are two foils with this texture. These are: Italian oak and Severo oak (ENDURO 3D).




# BIDIRECTIONAL FOIL WITH VERTICAL AND HORIZONTAL TEXTURE:

The combination of two previous types of texture. There is one foil of that type in the INVADO offer—Chestnut (ENDURO).

All 3 types of foils can be applied to foiled doors only. In case of modular doors, due to different construction, the texture direction of vertical and horizontal elements is different.




# **REBATED AND NON-REBATED DOORS:**



The edge of a **rebated door** leaf is finished with a rebate (visible in the picture A1) that overlaps a door frame when the door is closed. Door leaves made this way do not fit flush with a door frame.

The edge of a **non-rebated door** leaf has no additional finishing, i.e. it has a flat surface. Door leaves made this way fit flush with a door frame (A2).


# **LEFT AND RIGHT DOOR:**



Before buying a door, it is worth considering which direction it should be opening in. For safety reasons, bathroom or kitchen door should be installed in a way that makes it possible to open it outwards. In other areas, it is dependent on the users' preference and the layout of the apartment or the house. The next step is to determine which door we are looking for: right or left. What does it mean? If the hinges are installed on the right side of a door frame, that means we need a right door, if the opposite—we have to select the left door. Therefore, before going to the store it is worth to reconsider this question and write down a list of needed right and left doors, and to determine the opening direction for each of them.

# DOOR PRICE CALCULATION:

In most cases, the quoted prices are of a door leaf without a door frame or door handles. In order to obtain the full price of the door set, you have to use the following calculation:



# LEGEND



intensity of use: ••000

**ENDURO classification:** Foil of high-quality design and very good imitation of a natural wood structure. High durability. **Intended for:** buildings and living quarters with a wide range of use.







# **ECO-FORNIR FORTE**

european oak

severo oak



**ECO-VENEER FORTE classification**—high quality laminate in modern colours, very high durability. **CPL**—foil in modern colours. **Intended for:** hotels, offices, public buildings.

italian oak









naturo oak





B707






siberian larch

**ENDURO POLI** foil



B726

**Classification:** high quality polypropylene foil is characterised by excellent durability. **Intended for:** buildings and living quarters with a wide range of use



- ADJUSTABLE DOOR FRAMES,
  ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

Can be combined with all models and colours of interior doors INVADO



intensity of use:



# **AVAILABLE GLASS**







INDIVIDUAL BATCHES OF GLASS MAY VARY IN SHADE







# collection of MODULAR DOORS

COIGIO	
Artano	14
Aversa	14
Mirror	16
Lago	18
Pasaro	20
Vinadio	22
Fossano	24
Imperia	26
Destino Unico	28
Livata	30
Versano	32
Nogaro	34
Tamparo	36
Linea Forte	38
Capena Inserto	40
Martina	42
Domino	44
Bianco	46
Larina	48
D'Artagnan	50

# **Corato**















WATCH THE ASSEMBLY VIDEOS ON OUR YOUTUBE CHANNEL















17

47

# **AVAILABLE DECORS**

# **ENDURO** foil



# ENDURO 3D foil







# **ENDURO PLUS** foil



# **ECO-VENEER FORTE**









white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: 22 mm-thick panel
- filling element: panel or glass, depending on the model (4 mm-thick)
- 3
- the frame is made of MDF board upper part of the frame is 350 mm high, lower part of the frame is 400 mm high door leaf covered with ENDURO foil or ECO-VENEER 4
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES


- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARGED EXTRA

- door without a key hole door width "100"
- additional hinge for the door in sizes "60"-"80"
- additional hinge for non-rebated door—included in a door frame
- caps for hinges (chrome, satin chrome, golden, black)
- ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves) · automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

# AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)





standard—no extra charge



page 95	• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
page 97	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide
page 97	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide
naan 00 00	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES

# AVAILABLE OPTIONS OF DOOR LEAVES EXECUTION:

# Artano and Aversa

























1

4

# **AVAILABLE DECORS**

# **ENDURO** foil




# ENDURO 3D foil



# **ENDURO PLUS** foil









white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: 16 mm-thick panel (Artano) / 22 mm-thick panel (Aversa)
- 2 filling element: panel or glass, depending on the model (4 mm-thick)
- 3 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARGED EXTRA

_	door without a key hole	no outro observe
	door williout a key note	no extra charge
٠	door width "100"	
	additional bings for the door in sizes "40"—"80"	

- additional hinge for non-rebated door—included in a door frame caps for hinges (chrome, satin chrome, golden, black)
- ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version
- double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- · automatic bottom door seal, widths "60"-"100"
- · aluminum thresholds, widths: "60"-"100"

# AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



satinato—tempered glass

standard—no extra charge



[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95
[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	e page 97
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wire	de <b>page 97</b>
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99

# Mirror

























4

# **AVAILABLE DECORS**

# **ENDURO** foil



**ENDURO 3D** foil




# **ENDURO PLUS** foil









**ECO-VENEER CPL** 

B490 white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,

   ADJUSTABLE DOOR FRAMES,

   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: panel (6 mm-thick)
- filling element: mirror (4 mm-thick)
- 2 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\mbox{\sc hidden hinges}$  with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARCED EVERA

A	ADDITIONAL OPTIONS CHARGED EXTRA	
•	door without a key hole	no extra charge
•	door width "100"	
•	additional hinge for the door in sizes "60"-"80"	

- additional hinge for non-rebated door—included in a door frame
- caps for hinges (chrome, satin chrome, golden, black) ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version
- double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

# **AVAILABLE DOOR FRAMES**



page 98-9	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES
page 9	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide
page 9	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide
page 9	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
page 9	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 9	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)

1

3

Lago

AVAILABLE OPTIONS OF DOOR LEAVES EXECUTION: **REBATED**DOORS



SINGLE DOORS

**DOUBLE** 

DOORS FOR SLIDING SYSTEMS

DOORS WITH VENTILATION







# **AVAILABLE DECORS**


# **ENDURO** foil



ENDURO 3D foil



# **ENDURO PLUS** foil



# **ECO-VENEER FORTE**







white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: 22 mm-thick panel
- 2 filling element: panel or glass, depending on the model (4 mm-thick)
- 3 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94) width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\mbox{\sc hidden hinges}$  with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARGED EXTRA

 door without a key hole door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black) ventilation undercut

PVC ventilation sleeves

metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems

door made in a non-rebated version

double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

automatic bottom door seal, widths "60"-"100"

aluminum thresholds, widths: "60"-"100"

# $\begin{picture}(100,0) \put(0,0){$AVAILABLE} \put(0,0){$GLASS$} \put(0,0){$GLA$



# satinato—tempered glass

standard—no extra charge

1/

4



NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

# **Pasaro**

























17

47

# **AVAILABLE DECORS**

# **ENDURO** foil



ebony oak

ENDURO 3D foil







# **ENDURO PLUS** foil







**ECO-VENEER CPL** 



white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: 22 mm-thick panel
- filling element: panel or glass, depending on the model (4 mm-thick)
- 3
- the frame is made of MDF board upper part of the frame is 350 mm high, lower part of the frame is 400 mm high 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARGED EXTRA

door without a key hole

door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)

ventilation undercut

PVC ventilation sleeves

metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems

door made in a non-rebated version double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

automatic bottom door seal, widths "60"-"100"

aluminum thresholds, widths: "60"-"100"

# $\begin{picture}(100,0) \put(0,0){$AVAILABLE} \put(0,0){$GLASS$} \put(0,0){$GLA$



satinato—tempered glass

standard—no extra charge



page 95	• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	•
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	•
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	•
page 97	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	•
page 97	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	•
naan 00 00	A NOTE: THE OFFER ALSO INCLUDES METAL DOOR EDAMES	-

# Vinadio



**REBATED**DOORS

















# **AVAILABLE DECORS**

# **ENDURO** foil



**ENDURO 3D** foil











# **ENDURO PLUS** foil





duro walnut eterno oak grey oak



# **ECO-VENEER CPL** B490

white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: 22 mm-thick panel
- filling element: panel or glass, depending on the model (4 mm-thick)
- 2 the frame is made of MDF board
- door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARGED EXTRA

 door without a key hole door width "100" additional hinge for the door in sizes "60"-"80"

- additional hinge for non-rebated door—included in a door frame caps for hinges (chrome, satin chrome, golden, black)
- ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version
- double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

satinato—tempered glass

# AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)





	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
•	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
•	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99

47

1

2

standard—no extra charge

# Fossano





















# **ENDURO** foil



ENDURO 3D foil








# **ENDURO PLUS** foil









**ECO-VENEER CPL** 

white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: 22 mm-thick panel
- 2 filling element: panel or glass, depending on the model (4 mm-thick)
- 3 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARGED EXTRA

door without a key hole

door width "100"

• additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)

ventilation undercut PVC ventilation sleeves

metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems

door made in a non-rebated version double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

automatic bottom door seal, widths "60"-"100"

aluminum thresholds, widths: "60"-"100"

# AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



satinato—tempered glass

standard—no extra charge

1

47

2



•	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
•	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

# **Imperia**

























# **AVAILABLE DECORS**

# **ENDURO** foil



# ENDURO 3D foil



# **ENDURO PLUS** foil



# **ECO-VENEER FORTE**







white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: 22 mm-thick panel
- 2 filling element: panel or glass, depending on the model (4 mm-thick)
- 3
- the frame is made of MDF board upper part of the frame is 350 mm high, lower part of the frame is 400 mm high
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\mbox{\sc hidden hinges}$  with a 3-D regulation in the colour CHROME/MATT

# Α

DDITIONAL	<b>OPTIONS</b>	CHARGED	EXTRA

door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)

ventilation undercut

PVC ventilation sleeves

door without a key hole

metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems door made in a non-rebated version

double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

automatic bottom door seal, widths "60"-"100"

• aluminum thresholds, widths: "60"-"100"

# AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



satinato—tempered glass

standard—no extra charge

2

4

# **AVAILABLE DOOR FRAMES**

ONAL INFORMATION: ment and accessories—page 102–105



NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98-99
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

# **Destino Unico**





















One of the most popular models of INVADO doors—DESTINO UNICO—has been awarded a "Gold Medal". These door leaves are a bold combination of colours, that allows to create intriguing, stylized interiors.

Therefore we had no doubt, that this is the collection to be submitted to the prestigious "Gold Medal" contest, held at the International Poznań Fair BUDMA. The IPF "Gold Medal" is one of the most recognizable awards in the Polish market, which is given to innovative products of the highest quality. We are proud and we thank to all those involved in the production and sale of doors Destino Unico.

# **AVAILABLE DECORS**

# **ENDURO** foil



ENDURO 3D foil




# **ENDURO PLUS** foil



# **ECO-VENEER FORTE**







white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# **CONSTRUCTION**

- filling element: panel or glass, depending on the model (4 mm-thick)
- filling element: 22 mm-thick panel
- 2 3 4 the frame is made of MDF board
- double-sided glass insert—80 mm wide
- door leaf covered with ENDURO foil or ECO-VENEER side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
  - $\mbox{\sc hidden hinges}$  with a 3-D regulation in the colour CHROME/MATT

ADDITIONAL OPTIONS CHARGED EXTRA

door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)

ventilation undercut

PVC ventilation sleeves

door without a key hole

metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems

door made in a non-rebated version double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

automatic bottom door seal, widths "60"-"100"

aluminum thresholds, widths: "60"-"100"

# AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



AVAILABLE COLOURS OF GLASS INSERT:

9005 Soft

9005 7015

satinato—tempered glass

standard—no extra charge

17

2

5 /

4

3



page 95	• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
page 97	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide
page 97	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide
29_89 ann	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES

# Livata


























2

4

# **AVAILABLE DECORS**

# **ENDURO** foil



# ENDURO 3D foil




# **ENDURO PLUS** foil



# **ECO-VENEER FORTE**







white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: panel or glass, depending on the model (4 mm-thick)
- 2 filling element: 22 mm-thick panel
- 3 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARGED EXTRA

 door without a key hole door width "100" additional hinge for the door in sizes "60"-"80"

- additional hinge for non-rebated door—included in a door frame
- caps for hinges (chrome, satin chrome, golden, black) ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version
- double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

# AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)





standard—no extra charge



page 98-9	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES
page 9	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide
page 9	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide
page 9	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
page 9	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 9	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)

# Versano





















# **ENDURO** foil



ENDURO 3D foil











**ENDURO PLUS** foil



# **ECO-VENEER FORTE**







- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

B490

white

**ECO-VENEER CPL** 

# CONSTRUCTION

- filling element: 22 mm-thick panel
- filling element: panel or glass, depending on the model (4 mm-thick)
- 3
- the frame is made of MDF board, upper part of the frame is 350 mm high, lower part of the frame is 400 mm high
- door leaf covered with ENDURO foil or ECO-VENEER 4
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\mbox{\sc hidden hinges}$  with a 3-D regulation in the colour CHROME/MATT

ADDITIONAL OPTIONS CHARGED EXTRA

door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)

ventilation undercut PVC ventilation sleeves

metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems

door made in a non-rebated version

door without a key hole

double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

automatic bottom door seal, widths "60"-"100"

aluminum thresholds, widths: "60"-"100"

# AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



satinato—tempered glass

standard—no extra charge

1

2

4













# AVAILABLE OPTIONS OF DOOR LEAVES EXECUTION:

# Nogaro

























# **AVAILABLE DECORS**

# **ENDURO** foil




ENDURO 3D foil



# **ENDURO PLUS** foil









B490

white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# CONSTRUCTION

- filling element: 22 mm-thick panel
- 2 • filling element: panel or glass, depending on the model (4 mm-thick)
- 3 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

# STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

# STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
  - $\mbox{\sc hidden hinges}$  with a 3-D regulation in the colour CHROME/MATT

# ADDITIONAL OPTIONS CHARGED EXTRA

- door without a key hole door width "100"
- additional hinge for the door in sizes "60"-"80"
- additional hinge for non-rebated door—included in a door frame
- caps for hinges (chrome, satin chrome, golden, black)
- ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

# $\begin{picture}(100,0) \put(0,0){$AVAILABLE} \put(0,0){$GLASS$} \put(0,0){$GLA$



satinato—tempered glass

standard—no extra charge

# **AVAILABLE DOOR FRAMES**



<ul> <li>[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)</li> </ul>	page 95
[OR\$1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98-99

1 2

4

# **Tamparo**























#### **ENDURO** foil



#### ENDURO 3D foil



#### **ENDURO PLUS** foil



#### **ECO-VENEER FORTE**









- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- filling element: panel or glass, depending on the model (4 mm-thick)
- 2 filling element: 22 mm-thick panel
- 3 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

#### STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

### ADDITIONAL OPTIONS CHARGED EXTRA

 door without a key hole door width "100" additional hinge for the door in sizes "60"-"80"

- additional hinge for non-rebated door—included in a door frame caps for hinges (chrome, satin chrome, golden, black)
- ventilation undercut PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

#### AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



satinato—tempered glass

standard—no extra charge

2

4



NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

#### AVAILABLE OPTIONS OF DOOR LEAVES EXECUTION:

# Linea Forte




















#### **ENDURO** foil



ENDURO 3D foil



#### **ENDURO PLUS** foil



#### **ECO-VENEER FORTE**



duro walnut eterno oak grey oak



white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- filling element: 22 mm-thick panel
- 2 filling element: panel or glass, depending on the model (4 mm-thick)
- 3 the frame is made of MDF board
- door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- · rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

#### STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\textbf{hidden hinges} \ \text{with a 3-D regulation in the colour CHROME/MATT}$

ADDITIONAL OPTIONS CHARGED EXTRA

door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)

ventilation undercut

PVC ventilation sleeves

door without a key hole

metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems

door made in a non-rebated version

double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

· automatic bottom door seal, widths "60"-"100"

· aluminum thresholds, widths: "60"-"100"

### $\begin{picture}(20,0) \put(0,0){$AVAILABLE GLASS}$ (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE) \end{picture}$



#### satinato—tempered glass

standard—no extra charge

1

4



	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
•	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98-99

#### AVAILABLE OPTIONS OF DOOR LEAVES EXECUTION:

# Capena Inserto




















#### **ENDURO** foil



#### **ENDURO 3D** foil




#### **ENDURO PLUS** foil



#### **ECO-VENEER FORTE**







- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

B490

white

**ECO-VENEER CPL** 

#### CONSTRUCTION

- filling element: panel or glass, depending on the model (4 mm-thick)
- filling element: 22 mm-thick panel
- the frame is made of MDF board
- 2 3 4 ALU strip—8 mm
  - door leaf covered with ENDURO foil or ECO-VENEER side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

#### STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\mbox{\sc hidden hinges}$  with a 3-D regulation in the colour CHROME/MATT

#### ADDITIONAL OPTIONS CHARGED EXTRA

door without a key hole

door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)

ventilation undercut

PVC ventilation sleeves metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems

door made in a non-rebated version

double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

automatic bottom door seal, widths "60"-"100"

aluminum thresholds, widths: "60"-"100"

### AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



satinato—tempered glass

standard—no extra charge

17

5



•	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99
•	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
•	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

### Martina



















#### **ENDURO** foil



ENDURO 3D foil









#### **ENDURO PLUS** foil



#### **ECO-VENEER FORTE**





**ECO-VENEER CPL** 



white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- filling element: panel or glass, depending on the model (4 mm-thick)
- 2 • filling element: 22 mm-thick panel
- 3 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

#### STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

### ADDITIONAL OPTIONS CHARGED EXTRA

door without a key hole

door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)

ventilation undercut

PVC ventilation sleeves metal ventilation sleeves, round (chrome, golden)

metal ventilation sleeves, square (chrome, nickel)

door made in a non-rebated version for sliding systems

door made in a non-rebated version

double door

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

automatic bottom door seal, widths "60"-"100"

aluminum thresholds, widths: "60"-"100"

#### AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



satinato—tempered glass

standard—no extra charge

2

4



NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

### Domino



































4

#### **AVAILABLE DECORS**

#### **ENDURO** foil














#### **ENDURO PLUS** foil







**ECO-VENEER CPL** 



white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- filling element: 10 mm-thick panel
- 2 filling element: panel or glass, depending on the model (4 mm-thick)
- 3 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

#### STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

#### ADDITIONAL OPTIONS CHARGED EXTRA

•	door without a key hole	no e
•	door width "100"	
•	additional hinge for the door in sizes "60"-"80"	

- additional hinge for non-rebated door—included in a door frame
- caps for hinges (chrome, satin chrome, golden, black)
- ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version
- double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

#### AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)





standard—no extra charge



page 97
page 97
page 96
page 96
page 95

## Bianco




















#### **ECO-VENEER CPL**

B490

#### CONSTRUCTION

- filling element: MDF board (33 mm-thick)
- filling element: panel (10 mm-thick) or glass (4 mm-thick), depending on the model
- 2 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

#### STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

#### ADDITIONAL OPTIONS CHARGED EXTRA

- door without a key hole door width "100"
- additional hinge for the door in sizes "60"-"80"
- additional hinge for non-rebated door—included in a door frame
- caps for hinges (chrome, satin chrome, golden, black)
- ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version
- double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

### AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



#### satinato—tempered glass

standard—no extra charge

2

3

4

#### **AVAILABLE DOOR FRAMES**



•	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99
•	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
•	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

ENDURO POLI foil
Only available as a door frame colour for:

• BLOCK DOOR FRAMES,

• ADJUSTABLE DOOR FRAMES,

• ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

# Larina









































1

2

3

47

#### **AVAILABLE DECORS**

#### **ENDURO** foil





**ENDURO 3D** foil









#### **ENDURO PLUS** foil



#### **ECO-VENEER FORTE**





- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- filling element: MDF board (35 mm-thick)
- filling element: panel (10 mm-thick) or glass (4 mm-thick), depending on the model
- 2 the frame is made of MDF board
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT FOR REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

#### STANDARD EQUIPMENT FOR NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for a standard key or a WC knob, 85 mm for a cylinder lock insert
- $\,$  hidden hinges with a 3-D regulation in the colour CHROME/MATT

#### ADDITIONAL OPTIONS CHARGED EXTRA

 door without a key hole door width "100"

additional hinge for the door in sizes "60"-"80"

additional hinge for non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black)


ventilation undercut

PVC ventilation sleeves

- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- door made in a non-rebated version
- double door
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

#### AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)





standard—no extra charge



	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	page 97
•	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	page 97
•	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99

# **D'Artagnan**















2

door frame additional options—page 97

3








#### **AVAILABLE DECORS**

#### **ENDURO** foil



ebony



#### ENDURO PLUS foil

LIADO	KO I L	3 1011		
	+	+	1	ŀ
B705	B70	7	B708	
spring oak	winte oak		iberian arch	

#### **ECO-VENEER FORTE**



duro walnut eterno oak grey oak

#### **ECO-VENEER CPL**



white



- ENDURO POLI foil
  Only available as a door frame colour for:

   BLOCK DOOR FRAMES,

   ADJUSTABLE DOOR FRAMES,

   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- frame is made of finger joint pinewood, covered with MDF and HDF boards
- 2 • filling element: panel (10 mm-thick) or glass (6 mm-thick), depending on the model
  - door leaf covered with ENDURO foil or ECO-VENEER
- · side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT REBATED DOOR LEAVES

- lock 72 mm for a standard key, a WC knob or acylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

#### STANDARD EQUIPMENT NON-REBATED DOOR LEAVES

- magnetic lock 90 mm for standard key or WC knob and 85 mm for cylinder lock insert
- hidden hinges with regulation 3D in CHROME/MAT colour

#### **ADDITIONAL OPTIONS AT EXTRA CHARGE**

- door without a key hole no extra charae door width "100"
- additional hinge in door width from "60"-"80" additional hinge in non-rebated door
- caps for hinges
- ventilation undercut (model INTERO)
- door made in non-rebated version
- cylinder lock insert 31/36 (31/31 in non-rebated door leaves)
- aluminum thresholds, widths: "60"-"100"

#### AVAILABLE GLASS (THE MATT (ENGRAVED) SIDE OF GLASS IS LOCATED ON THE HINGE SIDE)



• s	atinato—tempered glass		no extra charge
•	longer execution time	transparent—tempered glass	no extra charge











page 95	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
page 97	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide
page 97	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide
naae 08_00	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES







# collection of FOILED DOORS

Salerno	54
Norma Decor	56
Torino	58
Merano	60
Lido	62
Dolce	64
Strada	66
Sagittarius	68
Gemini	70
Virgo	72
Parma	74
Orso	76
Libra	78
Taurus	78

# Salerno


























B462



B587

















B705

spring oak

B596

#### **ECO-VENEER CPL**

siberian larch



white

B707



#### **ENDURO POLI** foil

- Only available as a door frame colour for:

  BLOCK DOOR FRAME,

  ADJUSTABLE DOOR FRAME,

  ADJUSTABLE DOOR FRAME FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- the frame is made of MDF board
  - standard filling—"honeycomb"
- optional filling—chipboard
- frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole	no extra charge
door width "100"	•
additional hinge for the door in sizes "60"-"80"	
caps for hinges (chrome, satin chrome, golden, black)	•

- · ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- double door
- cylinder lock insert 31/36
- tubular chipboard filling
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



standard—no extra charae satinato







nage 09_00	NOTE: THE OFFER ALSO INCLUDES METAL DOOP FRAMES
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 95	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)

### **Norma Decor**


















#### PORTHOLE in NORMA DECOR 6:

available in silver and black colour with the possibility of using a transparent or satin glass pane option included in the price of the door leaf



#### ND2 and ND3 door leaves are available only in white [B134], beech [B136], oak [B224] and walnut [B339]

#### **AVAILABLE DECORS**



B541 B597 precious oak

**ENDURO PLUS foil** 

B587

B462

B598

B637 anthracite

B705

B639 B656 B657 european oak

B707 winter oak

B708

cedar forte naturo oak snowy oak spring oak **ECO-VENEER FORTE** 

B596

B473 B474 B476

duro walnut eterno oak grey oak

#### **ECO-VENEER CPL**

B490

white



#### **ENDURO POLI** foil

- Only available as a door frame colour for:

   BLOCK DOOR FRAME,

   ADJUSTABLE DOOR FRAME,

   ADJUSTABLE DOOR FRAME FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- the frame is made of MDF board
- standard filling—"honeycomb"
- optional filling—chipboard frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94) width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
caps for hinges (chrome, satin chrome, golden, black)	
ventilation undercut	***************************************

- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- double door
- cylinder lock insert 31/36
- tubular chipboard filling
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"
- ventilation grid

#### AVAILABLE GLASS THE MATT (ENGRAVED) SIDE OF GLASS—ON THE HINGES SIDE







ı	•	chinchilla	standard—no extra charge
	•	satinato	at extra charge
ľ	•	satinato or transparent—NORMA DECOR 6	no extra charge

#### **AVAILABLE DOOR FRAMES**





ADDITIONAL INFORMATION: equipment and accessories—page 102–105





•	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99

# Torino























B596

B587

B473 B474 B476 duro walnut eterno oak grey oak

#### **ECO-VENEER CPL**

B708

siberian larch



white

B707



B462

#### **ENDURO POLI** foil

B705

spring oak

- Only available as a door frame colour for:

  BLOCK DOOR FRAME,

  ADJUSTABLE DOOR FRAME,

  ADJUSTABLE DOOR FRAME FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- the frame is made of MDF board standard filling—"honeycomb" optional filling—chipboard frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE door without a key hole

door width "100"	
additional hinge for the door in sizes "60"-"80"	
caps for hinges (chrome, satin chrome, golden, black)	
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
aluminum thresholds, widths: "60"-"100"	
	additional hinge for the door in sizes "60"-"80" caps for hinges (chrome, satin chrome, golden, black) ventilation undercut PVC ventilation sleeves metal ventilation sleeves, round (chrome, golden) metal ventilation sleeves, square (chrome, nickel) door made in a non-rebated version for sliding systems double door cylinder lock insert 31/36 tubular chipboard filling automatic bottom door seal, widths "60"-"100"

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)





•	satinato	standard—no extra charge
•	chinchilla	standard—no extra charge

#### **AVAILABLE DOOR FRAMES**







	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98-99
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

no extra charge

### Merano



































duro walnut eterno oak grey oak

#### **ECO-VENEER CPL**



white



#### **ENDURO POLI** foil

- Only available as a door frame colour for:

  BLOCK DOOR FRAME,

  ADJUSTABLE DOOR FRAME,

  ADJUSTABLE DOOR FRAME FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- the frame is made of MDF board
   standard filling—"honeycomb"
   optional filling—chipboard optional filling—chipboard frame with filling is covered with HDF boards on both sides door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

tubular chipboard filling

• automatic bottom door seal, widths "60"-"100" • aluminum thresholds, widths: "60"-"100"

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

### ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole	no extra charge
door width "100"	•
additional hinge for the door in sizes "60"-"80"	•
caps for hinges (chrome, satin chrome, golden, black)	•
ventilation undercut	•
PVC ventilation sleeves	***************************************
metal ventilation sleeves, round (chrome, golden)	***************************************
metal ventilation sleeves, square (chrome, nickel)	***************************************
door made in a non-rebated version for sliding systems	***************************************
double door	***************************************
cylinder lock insert 31/36	***************************************

### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)





•	satinato	standard—no extra charge
	chinchilla	standard—no extra charge

#### **AVAILABLE DOOR FRAMES**

ADDITIONAL INFORMATION: equipment and accessories—page 102–105







[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95
[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98–99
































**ECO-VENEER CPL** 

B490

white

#### **ENDURO POLI** foil

- Only available as a door frame colour for:

   BLOCK DOOR FRAME,

   ADJUSTABLE DOOR FRAME,

   ADJUSTABLE DOOR FRAME FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- the frame is made of MDF board
   siandard filling—tubular chipboard
   frame with filling is covered with HDF boards on both
   door leaf covered with ENDURO foil or ECO-VENEER frame with filling is covered with HDF boards on both sides
- ALU strip width—8 mm
- side edges and upper edge are foiled rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

- lock 72 mm for standard key, WC knob or cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs in door leaves "60"—"80", 3 pcs in door leaves "90"—"100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole	no extra charge
door width "100"	•
additional hinge in door width from "60"—"80"	
caps for hinges	
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in non-rebated version for sliding systems	
double door	

#### cylinder lock insert 31/36 automatic door bottom seal, widths "60"-"100"

• aluminum thresholds, widths: "60"—"100"



	NOTE, THE OFFER ALSO INCLUDES METAL DOOD FRAMES	00 00
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

2

# Dolce
























#### **ENDURO 3D** foil



#### **ENDURO PLUS foil**



#### **ECO-VENEER FORTE**



duro walnut eterno oak grey oak







#### **ENDURO POLI** foil

- Only available as a door frame colour for:

  BLOCK DOOR FRAMES,

  ADJUSTABLE DOOR FRAMES,

  ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

#### CONSTRUCTION

- the frame is made of MDF board
  - standard filling—"honeycomb"
- optional filling—chipboard
  - frame with filling is covered with HDF boards on both sides
  - door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole	no extra charge
• door width "100"	•
additional hinge for the door in sizes "60"-"80"	•
caps for hinges (chrome, satin chrome, golden, black)	•
ventilation undercut	•
PVC ventilation sleeves	•
metal ventilation sleeves, round (chrome, golden)	•
metal ventilation sleeves, square (chrome, nickel)	•
door made in a non-rebated version for sliding systems	***************************************

#### double door cylinder lock insert 31/36

- tubular chipboard filling
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



standard—no extra charge satinato



page 95	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
	NOTE THE OFFER ALSO MOUNTS HET ALDOOD FRANCE

### Strada






















B288 chestnut



### **ENDURO POLI** foil

#### **ENDURO 3D** foil







#### **ECO-VENEER FORTE**



duro walnut eterno oak grey oak

### **ECO-VENEER CPL** B490

white

#### CONSTRUCTION

- 1 2 3 4 5 the frame is made of MDF board standard filling—"honeycomb" optional filling—chipboard frame with filling is covered with HDF boards on both sides door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole	no extra charge
door width "100"	•
additional hinge for the door in sizes "60"—"80"	
caps for hinges (chrome, satin chrome, golden, black)	
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	•
aluminum thresholds, widths: "60"-"100"	***************************************

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



#### satinato

standard—no extra charge



_	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	naac 00 00
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

# **Sagittarius**






















B288 chestnut



#### **ENDURO 3D** foil



#### **ENDURO PLUS** foi



#### **ECO-VENEER FORTE**





### **ECO-VENEER CPL**

B490 white

#### CONSTRUCTION

- 1 2 3 4 5 the frame is made of MDF board standard filling—"honeycomb" optional filling—chipboard frame with filling is covered with HDF boards on both sides door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole	no extra charge
door width "100"	•
additional hinge for the door in sizes "60"—"80"	
caps for hinges (chrome, satin chrome, golden, black)	
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
aluminum thresholds, widths: "60"—"100"	

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



#### satinato

standard—no extra charge



_	NOTE, THE OFFER ALSO INCLUDES METAL DOOD FRAMES	00 00
•	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
•	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
•	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

### Gemini

























B288 chestnut

ENDURO 3D foil



### **ENDURO POLI** foil

30







duro walnut eterno oak grey oak



**D** 

**ECO-VENEER CPL** 

B490 white

#### CONSTRUCTION

- the frame is made of MDF board
  - standard filling—"honeycomb" optional filling—chipboard
  - frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled

• automatic bottom door seal, widths "60"-"100" • aluminum thresholds, widths: "60"—"100"

- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

door without a key hole

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

• d	oor width "100"
• a	dditional hinge for the door in sizes "60"–"80"
• C	aps for hinges (chrome, satin chrome, golden, black)
• V	entilation undercut
• P	/C ventilation sleeves
• m	etal ventilation sleeves, round (chrome, golden)
• m	etal ventilation sleeves, square (chrome, nickel)
• d	oor made in a non-rebated version for sliding systems
• d	ouble door
• C	ylinder lock insert 31/36
• tu	bular chipboard fillina

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



satinato

standard—no extra charge

no extra charge



naan 00 00	. NOTE: THE OFFER ALSO INCLUDES METAL DOOD EDAMES
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 95	• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)

# Virgo






















#### **AVAILABLE DECORS**



B288 chestnut

ENDURO 3D foil **D** 30



B587 B596 B707 siberian larch cedar forte naturo oak snowy oak spring oak winter oak

**ECO-VENEER FORTE** 



duro walnut eterno oak grey oak



B490 white

#### CONSTRUCTION

- the frame is made of MDF board standard filling—"honeycomb" optional filling—chipboard frame with filling is covered with HDF boards on both sides door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

· door without a key hole

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

 door width "100"
additional hinge for the door in sizes "60"-"80"
 caps for hinges (chrome, satin chrome, golden, black)
 ventilation undercut
 PVC ventilation sleeves
 metal ventilation sleeves, round (chrome, golden)
 metal ventilation sleeves, square (chrome, nickel)
 door made in a non-rebated version for sliding systems
 double door
 cylinder lock insert 31/36
 tubular chipboard filling
 automatic bottom door seal, widths "60"-"100"
 aluminum thresholds, widths: "60"—"100"

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



standard—no extra charge satinato

#### **AVAILABLE DOOR FRAMES**



NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	nago 99 99
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95

no extra charge

# **Parma**






















#### **AVAILABLE DECORS**



B288 chestnut







#### **ECO-VENEER FORTE**





# **ECO-VENEER CPL**

B490 white

#### CONSTRUCTION

- the frame is made of MDF board
- standard filling—"honeycomb" optional filling—chipboard
- frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

door without a key hole

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

•	door width "100"
•	additional hinge for the door in sizes "60"—"80"
•	caps for hinges (chrome, satin chrome, golden, black)
•	ventilation undercut
•	PVC ventilation sleeves
•	metal ventilation sleeves, round (chrome, golden)
•	metal ventilation sleeves, square (chrome, nickel)
•	door made in a non-rebated version for sliding systems
	double door

#### · cylinder lock insert 31/36

- tubular chipboard filling
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

#### AVAILABLE GLASS (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



standard—no extra charge satinato

#### **AVAILABLE DOOR FRAMES**





• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	page 95
[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	page 96
[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	page 96
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	page 98-99

no extra charge

# **Orso**


























#### **AVAILABLE DECORS**



#### CONSTRUCTION

- the frame is made of MDF board
  - standard filling—"honeycomb"
- optional filling—chipboard
- frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

## STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

## ENDURO 3D foil

B288 chestnut















duro walnut eterno oak grey oak

#### siberian larch winter oak **ECO-VENEER CPL**



white

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

	door without a key hole
•	door width "100"

- additional hinge for the door in sizes "60"-"80"
- caps for hinges (chrome, satin chrome, golden, black)
- ventilation undercut
- PVC ventilation sleeves
- metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- double door
- cylinder lock insert 31/36
- tubular chipboard filling
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



standard—no extra charge satinato

#### **AVAILABLE DOOR FRAMES**







page 95	• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide	
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide	
page 98–99	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	

no extra charge

# ibra and Taurus













WATCH THE ASSEMBLY VIDEOS ON OUR YOUTUBE CHANNEL









## TAURUS door leaves are available only in CHESTNUT [B288]

#### **AVAILABLE DECORS ENDURO** foil B134 B136 B224 B339 B402 B406

oak

lindo (white) beech

B288 chestnut



walnut

coimbra

## **ENDURO POLI** foil

ebony

B706

#### ENDURO 3D foil **D 3**D B597 B637 ashy oak anthracite seve oak classic walnut

**ENDURO PLUS** foil B596 B705 B587 B707

cedar forte naturo oak snowy oak spring oak



duro walnut eterno oak grey oak

#### siberian larch winter oak **ECO-VENEER CPL**

B490 white

#### CONSTRUCTION

- the frame is made of MDF board
  - standard filling—"honeycomb" optional filling—chipboard
- frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on page 94)
- in case of double doors, there is a covering strip (drawing on page 94)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

#### STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"-"80", 3 pcs for door leaves in sizes "90" and "100"

## ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	

- · caps for hinges (chrome, satin chrome, golden, black) · ventilation undercut
- PVC ventilation sleeves metal ventilation sleeves, round (chrome, golden)
- metal ventilation sleeves, square (chrome, nickel)
- door made in a non-rebated version for sliding systems
- double door
- cylinder lock insert 31/36
- tubular chipboard filling
- automatic bottom door seal, widths "60"-"100"
- aluminum thresholds, widths: "60"-"100"

#### **AVAILABLE GLASS** (THE GLOSSY SIDE OF GLASS IS ON THE HINGE SIDE)



standard—no extra charge satinato

#### **AVAILABLE DOOR FRAMES**







page 95	• [OB3] block door frame (possibility to add an architrave $10 \times 60 \text{ mm}$ or $16 \times 80 \text{ mm}$ )
page 96	[ORS1] adjustable door frame with a flat angle architrave 60 mm-wide
page 96	[ORS8] adjustable door frame with a flat angle architrave 80 mm-wide
page 98–99	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES

# **Amber**











# Amber 13



GROUP I









#### CONSTRUCTION

- GLASS PANE: tempered, 8 mm-thick
- the matt side of a glass pane is on the hinge side
- block or adjustable door frame, 2 hinges
- GLASS PANES SHOULD BE ORDERED TOGETHER WITH THE DOOR FRAME

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

· ventilation undercut

#### **LOCK TYPES**

1	door handle "hidden", lock without a hole
2	door handle "protrude", lock without a hole
3	standard key lock
4	cylinder lock insert
5	WC lock

#### AMBER DOORS ARE DIVIDED INTO GROUPS DUE TO THE TYPES OF GLASS DECORATIONS

	Amber 13—satinato glass	
GROUP I—basic glass (transparent or matte in various shades)	Amber 14—transparent glass	
, i	Amber 15—transparent glass—graphite	

	Amber 3—overprint on transparent glass
(engraving or overprint)	Amber 6—overprint on transparent glass
	Amber 12—engraving on satinato glass

DIMENSIONS OF GLASS DOORS	"60"	"70"	"80"	"90"
door leaf width	617	717	817	917
door leaf height	(PL) 2027 / 1975 (CZ/SK)			















#### **AVAILABLE COLORS**







#### **AVAILABLE DOOR FRAMES**



• [OB3]—block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	info—page 95
• [ORS1]—adjustable door frame with a flat angle architrave 60 mm-wide	info—page 96
 • [ORS8]—adjustable door frame with a flat angle architrave 80 mm-wide	info—page 96

# Norma Decor and Libra











#### **AVAILABLE DECORS**

#### **ENDURO** foli





#### **ENDURO PLUS** foli





#### **ECO-VENEER CPL**



duro walnut eterno oak grey oak



#### **ENDURO POLI** foil

Only available as a door frame colour for:
BLOCK DOOR FRAMES,
ADJUSTABLE DOOR FRAMES,

- ADJUSTABLE DOOR FRAMES,
   ADJUSTABLE DOOR FRAMES FOR NON-REBATED MODULAR DOORS

#### **CONSTRUCTION**

- folding doors consist of a folding door and a block or adjustable door frame
- construction of each half of the folding door consists of a frame made of MDF board or 33 mm thick semi-finished coniferous wood glued in layers.
- 2 filling—"honeycomb"
- 3 frame and filling are covered with 3 mm-thick MDF boards
- 4 door leaf covered with ENDURO foil or ECO-VENEER
- each half of a door leaf has a rabbet along the vertical edge
- both parts of a door leaf are joined together with hidden hinges
- the door leaf is connected to the floor with a spigot fixed in the holder, which is bolted to the floor
- the upper part is connected to the door frame with a spigot fixed in the holder, which is mounted in the rail bolted to the upper element of door frame
- the sliding mechanism (trolley), mounted in the rail, stabilizes the door leaf when opening and closing
- rounded vertical edges of door leaves (more info on page 94)
- universal door leaf ready to be mounted on the left or right side
- width of single doors: "60"-"90"

#### STANDARD EQUIPMENT

- 2 silver round grips in color silver
- 2 hidden hinges in color silver

#### AVAILABLE GLASS (THE MATT SIDE OF GLASS IS ON THE HINGE SIDE)



satinato

standard—no extra charge

#### AVAILABLE DOOR FRAMES









• [OB3] block door frame (possibility to add an architrave  $10 \times 60 \text{ mm}$  or  $16 \times 80 \text{ mm}$ )

 [ORS1] adjustable door frame with a flat angle architrave 60 mm-wide page 96

• [ORS8] adjustable door frame with a flat angle architrave 80 mm-wide

page 95

page 98

# Pocket door sliding system
















#### DIAGRAM OF THE LOCATION OF DOOR FRAME ELEMENTS FOR SLIDING SYSTEM—SINGLE SLIDING SYSTEM






IMENSIONS OF THE CASS	ETTE FOR SINGLE SLIDING SYS	STEM (m	m)	DOOI	R LEAF DIMEN	SIONS	
internal width L x H	outer width C x H1	Α	В	wall thickness	width	height	
610 x 2075 (PL) / 2025 (CZ-SK)	1346 x 2115 (PL) / 2065 (CZ-SK)	670	640		644		
710 x 2075 (PL) / 2025 (CZ-SK)	1546 x 2115 (PL) / 2065 (CZ-SK)	770	740		744	2040 (PL)	
810 x 2075 (PL) / 2025 (CZ-SK)	1746 x 2115 (PL) / 2065 (CZ-SK)	870	840	100–125	844	- 1	
910 x 2075 (PL) / 2025 (CZ-SK)	1946 x 2115 (PL) / 2065 (CZ-SK)	970	940	-	944	1988 (CZ-SK	
1010 x 2075 (PL) / 2025 (CZ-SK)	2146 x 2115 (PL) / 2065 (CZ-SK)	1070	1040		1044		

#### DIAGRAM OF THE LOCATION OF DOOR FRAME ELEMENTS FOR SLIDING SYSTEM—DOUBLE SLIDING SYSTEM







SETTE FOR DOUBLE SLIDING S	YSTEM	(mm)	DOOR	LEAF DIMEN	SIONS
outer width C x H1	A	В	wall thickness	width	height
2610 x 2115 (PL) / 2065 (CZ-SK)	1290	640		644	
3010 x 2115 (PL) / 2065 (CZ-SK)	1490	740		744	2040 (PL)
3410 x 2115 (PL) / 2065 (CZ-SK) 1	1690	840	100-125	844	
3810 x 2115 (PL) / 2065 (CZ-SK)	1890	940		944	1988 (CZ-SK)
4210 x 2115 (PL) / 2065 (CZ-SK)	2090	1040	Ī	1044	
	outer width C x H1  2610 x 2115 (Pt) / 2065 (Cz-sk)  3010 x 2115 (Pt) / 2065 (Cz-sk)  3410 x 2115 (Pt) / 2065 (Cz-sk)  3810 x 2115 (Pt) / 2065 (Cz-sk)	outer width C x H1  2610 x 2115 (Pt.) / 2065 (Cz-sk)  3010 x 2115 (Pt.) / 2065 (Cz-sk)  1490  3410 x 2115 (Pt.) / 2065 (Cz-sk)  1690  3810 x 2115 (Pt.) / 2065 (Cz-sk)  1890	2610 x 2115 (PL) / 2065 (CZ-SK) 1290 640 3010 x 2115 (PL) / 2065 (CZ-SK) 1490 740 3410 x 2115 (PL) / 2065 (CZ-SK) 1690 840 3810 x 2115 (PL) / 2065 (CZ-SK) 1890 940	outer width C x H1         A         B         wall thickness           2610 x 2115 (Pt) / 2065 (cz-sk)         1290         640           3010 x 2115 (Pt) / 2065 (cz-sk)         1490         740           3410 x 2115 (Pt) / 2065 (cz-sk)         1690         840         100–125           3810 x 2115 (Pt) / 2065 (cz-sk)         1890         940	outer width C x H1         A         B         wall thickness         width           2610 x 2115 (PL) / 2065 (cz-sk)         1290         640         644           3010 x 2115 (PL) / 2065 (cz-sk)         1490         740         744           3410 x 2115 (PL) / 2065 (cz-sk)         1690         840         100–125         844           3810 x 2115 (PL) / 2065 (cz-sk)         1890         940         944

#### DIAGRAM OF LOCATION OF DOOR FRAME ENLARGING ELEMENTS FOR THE SLIDING DOOR POCKET SYSTEM








Adjustment of more than 20 mm is done by enlarging element (tunnel—at extra charge)

#### CASSETTE ELEMENTS: (A—upper profle + angle architrave / B—vertical profle + angle architrave / C—fender beam + angle architrave)



#### STANDARD EQUIPMENT (THE SET INCLUDES)

- construction casette for sliding system in sizes "100" or "125"
- set of profiles (door frame), brushes and seals
- set of covering profiles for both sides of the door frame
- grip (chrome, satin, golden or black)

#### **ADDITIONAL OPTIONS AT EXTRA CHARGE**

- soft-close hardware for sliding door
- key hook lock or WC hook lock (chrome, satin, golden, black) with a grip suitable for key or WC lock. In case of door leaves equipped with a hook lock, the customer installs the striking plate in the door frame on their own
  - tunnel (door frame enlarging element)—price per each 10 mm
- strike plate

The cassette 100 mm-wide is designed for modular door leaves (eg. Domino, Versano, Tamparo) and standard flat doors NORMA DÉCOR 1 and TAURUS. The cassette 125 mm-wide is designed for standard foiled door leaves (eg Torino, Strada).

KFY

WC lock

















# **Wall-mounted sliding system**










All foiled and modular door leaves can be installed as a wall-mounted sliding system. AMBER door leaves are not suitable for the wall-mounted sliding system.




YOUTUBE CHANNEL: ASSEMBLY AND INSTALLATION OF WALL-MOUNTED









OR FRAME -WALL SLIDING S leaf width n of the wall opening* r width of the door frame		" <b>60</b> "	" <b>70</b> "	"80"	"90"	"100"	"120"								
n of the wall opening*			744				120	"130"	"140"	"150	"160"	"170"	"180"	"190"	"200"
		7-4		844	944	1044	1288	1388	1488	1588	1688	1788	1888	1988	2088
r width of the door fran	•	674	774	874	974	1074	1294	1394	1494	1594	1694	1794	1894	1994	2094
	ime	644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
nal width of the door fr	frame	600	700	800	900	1000	1220	1320	1420	1520	1620	1720	1820	1920	2020
width of the door frame with architraves	60 mm <b>[ORS3]</b>	744	844	944	1044	1144	1364	1464	1564	1664	1764	1864	1964	2064	2164
	80 mm <b>[ORS9]</b>	784	884	984	1084	1184	1404	1504	1604	1704	1804	1904	2004	2104	2204
leaf height				*			(	PL) 2040 /	1988 <b>(CZ-S</b>	K)	÷	â	·	<u> </u>	-
ht of the wall opening							(1	PL) 2062 / :	2008 <b>(cz-si</b>	()					
r height of the door fro	ame						(1	PL) 2047 /	1993 <b>(cz-si</b>	()					
nal height of the door	frame*		•	•			(1	PL) 2025 /	1971 <b>(cz-si</b>	()		•	***************************************		
ht of the door frame	60 mm <b>[ORS3]</b>		•				(1	PL) 2097 / :	2043 <b>(cz-s</b> i	()	•		***************************************		•
with architraves 80 mm [ORS9]				***************************************			(1	- P <b>L)</b> 2117 / :	2063 <b>(cz-s</b> i	()		***************************************	***************************************		
r h	neight of the door from	neight of the door frame all height of the door frame* of the door frame 60 mm [ORS3] chitraves 80 mm [ORS9]	neight of the door frame all height of the door frame* of the door frame  60 mm [ORS3]	neight of the door frame all height of the door frame* of the door frame 60 mm [ORS3] chitraves 80 mm [ORS9]	neight of the door frame all height of the door frame* of the door frame  60 mm [ORS3]	neight of the door frame al height of the door frame* of the door frame  60 mm [ORS3]	neight of the door frame al height of the door frame* 60 mm [ORS3]	neight of the door frame (I) I height of the door frame* (I) I height of the door frame	neight of the door frame (PL) 2047 / of the door frame* (PL) 2077 / of the door frame 60 mm [ORS3] (PL) 2097 / of the door frame	neight of the door frame (PL) 2047 / 1993 (CZ-si al height of the door frame* (PL) 2025 / 1971 (CZ-si of the door frame 60 mm [ORS3] (PL) 2097 / 2043 (CZ-si	neight of the door frame (PL) 2047 / 1993 (CZ-SK) al height of the door frame* (PL) 2025 / 1971 (CZ-SK) of the door frame 60 mm [ORS3] (PL) 2097 / 2043 (CZ-SK)	neight of the door frame (PL) 2047 / 1993 (CZ-SK) al height of the door frame* (PL) 2025 / 1971 (CZ-SK) of the door frame 60 mm [ORS3] (PL) 2097 / 2043 (CZ-SK)	neight of the door frame (PL) 2047 / 1993 (CZ-SK) al height of the door frame* (PL) 2025 / 1971 (CZ-SK) of the door frame 60 mm [ORS3] (PL) 2097 / 2043 (CZ-SK)	neight of the door frame (PL) 2047 / 1993 (CZ-SK) al height of the door frame* (PL) 2025 / 1971 (CZ-SK) (PL) 2097 / 2043 (CZ-SK)	neight of the door frame  (PL) 2047 / 1993 (CZ-SK)  It height of the door frame*  (PL) 2025 / 1971 (CZ-SK)  (PL) 2097 / 2043 (CZ-SK)

CLASSIFICATION OF RAILS AND RAIL COVERS DEPENDING ON THE WIDTH OF THE SLIDING SYSTEM

door leaf  "60"  "70"  "80"  "90"  "100"  "60" + "60"  "40" + "77"	length of rail cover	number of rails and angle architraves	door leaf	length of rail cover	number of rails and angle architraves			
"60"	1350 mm		"70" + "70" or "60" + "80"	3000 mm				
"70"	1550 mm	200 cm-long	"70" + "80" or "60" + "90"	3200 mm				
"80"	1750 mm		"80" + "80" or "70" + "90" or "60" + "100"	3400 mm	2 rails and angle architraves			
"90"	1950 mm		"80" + "90" or "70" + "100"	3600 mm	200 cm-long			
"100"	2150 mm		"90" + "90" or "80" + "100"	3800 mm				
"60" + "60"	2600 mm	2 rails and angle architraves 200 cm-long	"90" + "100"	4000 mm				
"60" + "70"	2800 mm		"100" + "100"	4200 mm	3 rails and angle architraves 200 cm-loi			

#### STANDARD EQUIPMENT (THE SET INCLUDES)

- rail cover in the door leaf decor—installed on ALU strip (two types, depending on the width of the masking angle architrave used in the door frame—60 mm or 80 mm)
- thimble—1 piece (chrome, satin, golden, black)
- grip—chrome, satin, golden, black—a set for both sides of door leaf and thimble—1 piece (chrome, satin, golden, black)

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

- soft-close hardware for sliding door
- ENDURO / PLUS / 3D ECO-VENEER • KEY key hook lock or WC hook lock (chrome, satin, golden, black) with a grip suitable for key or WC lock
  - Rail cover dimensions:

**A**—91.5 mm **[ORS3]** lub 111.5 mm **[ORS9] B**—92 mm















grip and a thimble









#### **AVAILABLE DOOR FRAMES**



- [ORS3] adjustable door frame with a flat angle architrave 60 mm-wide the set includes: door frame and bumper with milling and striking plate
- [ORS9] adjustable door frame with a flat angle architrave 80 mm-wide the set includes: door frame and bumper with milling and striking plate

# **Egida (RC2)**













1

4

2

3





#### **AVAILABLE DECORS**





#### **ENDURO PLUS** foil





duro walnut eterno oak grey oak



# **CONSTRUCTION**

- frame is made of plywood
- filling element: tubular chipboard
- frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- door leaf thickness: 40 mm
- rounded vertical edges of door leaves (more info on page 94)
- width of single doors: "80"-"100"

#### STANDARD EQUIPMENT

- multipoint strip lock with 3 security bolts
- 3 reinforced hinges + 3 anti-burglary pins
- acoustic insulation Rw = 29 dB (acoustic insulation class Rw = 27 dB)
- ANTI-BURGLARY resistance class RC2
- · fixed aluminum threshold

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

- handle + QUEBECK shield—anti-burglary resistance class II (color INOX and TITAN)
- handle + ROYAL shield—anti-burglary resistance class III (color INOX)
- set of WILKA cylinder lock inserts (insert + insert with a knob), ANTI-BURGLARY resistance class 2, 30  $\times$  40 mm, 6 keys
- · panoramic viewfinder
- automatic door bottom seal for doors "80"-"100" cm width

## ATTENTION: automatic bottom door seal not applicable for doors with fixed threshold, therefore it is not included in the set.

<b></b>	AFNICIONIC	wooden	door fram	e [KOBA]	metal d	loor frame	[KOBM	
אוט	MENSIONS	"80"	"90"	"100"	"80"	"90"	"100"	
s1	door leaf width	844	944	1044	844	944	1044	
s2	width of wall opening	920	1020	1120	890	990	1090	
s3	outer width of door frame	890	990	1090	880	980	1080	
s4	internal width of door frame	802	902	1002	800	900	1000	
s5	width of door frame with architraves				906	1006	1106	
h1	door leaf height	(PL) 2	2040 / 1988 <b>(</b>	CZ-SK)	2040			
h2	internal height of door frame	(PL) 2	2084 / 2030 (	CZ-SK)		2070	•	
h3	outer height of door frame	(PL) 2	2069 / 2015 <b>(</b>		2064			
h4	internal height of door frame	(PL) 2	2025 / 1971 <b>(</b>	CZ-SK)		2024		
h5	height of door frame with architraves				2077			

#### **AVAILABLE DOOR FRAMES**





• [KOBA]—block door frame:

90 x 44 mm made of plywood covered with MDF board—width "80"-"100"

[KOBM]—metal door frame in RAL color: available as standard in brown color (8017) other colors—honey (8003), white (9010), beige (1001) and grey (7047)\*—width "80"-"100"


\*ATTENTION: Metal door frame in non-standard decors are available on request with longer production time.

# resistance El<sub>2</sub> 30 gnis









Fire doors should be a subject of technical inspections and maintenance operations in accordance with the rules set out in the applicable standards and regulations on fire-resistance doors. Technical and maintenance inspections should be carried out at least once a year.

#### APPLICATION:

IGNIS fire doors are flush, rebated, and single door leaves with fire resistance  $\rm El_2$  30. The door frame is made of non-flammable chipboard. Door leaf and door frame made of nonflammable chipboard can be installed in walls with fire resistance class  $\rm El_2$  30 according to PN-EN 13501-2: 2016 and min. density 575 kg/m³, in case of masonry walls made of ceramic or silicate bricks with min. thickness of 115 mm, concrete or reinforced concrete walls with min.

or silicate bricks with min. thickness of 115 mm, concrete or reinforced concrete walls with min thickness of 115 mm and walls made from blocks or cellular concrete blocks with min. thickness of 115 mm.

The doorset is supplied with:

- cylinder insert according to requirements of PN-EN 1303: 2015-07,
   self-closer according to requirements of PN-EN 1154: 1999 / AC: 2010P,
- self-closer according to requirements of PN-EN 1154: 1999 / AC: 2010P,
   complete door handle according to requirements of PN-EN 1906: 2012.

IGNIS DOOR LEAVES ARE SOLD ONLY AS A SET WITH A DOOR FRAME, A CYLINDER INSERT, A SELF CLOSER AND A HANDLE







#### **AVAILABLE DECORS**





**ENDURO 3D** foil

















B490

**ECO-VENEER CPL** 

#### **ECO-VENEER FORTE**



duro walnut eterno oak grey oak



#### **CONSTRUCTION**

- · frame: laminated pinewood
- filling: mineral wool
- frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEER
- door leaf thickness: 40 mm
- rounded vertical edges of door leaves (more info on page 94)
- width of single doors: "60"-"100"

#### STANDARD EQUIPMENT

- set of intumescent seals
- 3 screw-in pivot hinges

#### REQUIRED EQUIPMENT AT EXTRA CHARGE

- door leaf width "100"
- cylinder lock insert
- self-closer
- UNO door handle

#### **DIMENSIONS** "60" "70" "80" "90" "100" 744 944 1044 s1 door leaf width 644 844 796 996 s2 width of wall opening 696 896 1096 s3 outer width of door frame 666 766 866 966 1066 s4 internal width of door frame 600 700 800 900 1000 s5 width of door frame with architraves 1044 744 844 944 1144 (PL) 2040 / 1987 (CZ-SK) h1 door leaf height h2 internal height of door frame (PL) 2062 / 2007 (CZ-SK) h3 outer height of door frame (PL) 2047 / 1992 (CZ-SK) h4 internal height of door frame (PL) 2025 / 1970 (CZ-SK)

#### **AVAILABLE DOOR FRAMES**



[ORS1/E] adjustable door frame made of chipboard

symbol	В	С	D	E	F	G	Н	l
wall thickness	100–119	120–139	140–159	160–179	180–199	200–219	220–239	240–259
symbol	J	K	L	M	N	0		P
wall thickness	260–279	280–299	300–319	320–339	340–359	360–379	380-	-399

height of door frame with architraves

(PL) 2097 / 2042 (CZ-SK)

2

wooden interior entrance doors of **HALSPAN** system













TECHNICAL DOORS GUARDIA ARE CERTIFIED TO BE SOLD IN POLAND, RUSSIA, BELARUS, KAZAKHSTAN AND GEORGIA



1

4

2

3 /



Fire doors should be a subject of technical inspections and maintenance operations in accordance with the rules set out in the applicable standards and regulations on fire-resistance doors. Technical and maintenance inspections should be carried out at least once a year.

#### APPLICATION:

Doors according to Halspan system are intended for use in residential and public buildings as interior doors to the extent resulting from their performance characteristics set out in point 3 of the National Technical Assessment ITB-KOT-2018/0407, 1st edition. The doors have a NATIONAL CERTIFICATE OF STABLE PERFORMANCE No. AC 158-UWB-W1355.

Acoustic insulation index for

**GUARDIA El<sub>2</sub>30 i El<sub>2</sub>60:** Rw=32 db—Single door leaves El<sub>2</sub> 30 and El<sub>2</sub> 60

Rw=32 db—Double door leaf El<sub>2</sub> 60 Rw=27 db—Double door leaf El<sub>2</sub> 30

Fire resistance: El,30 (30 min), El,60 (60 min)

The doorset is supplied with:

- cylinder insert according to requirements of PN-EN 1303: 2015-07,
- self-closer according to requirements of PN-EN 1154: 1999 / AC: 2010P,
- complete door handle according to requirements of PN-EN 1906: 2012,
- closing sequence controller according to requirements of PN-EN 1158: 1999 / AC: 2006P (for double doors only).

ATTENTION: the seller's obligation is to sell technical doors equipped with above elements (at extra charge)

#### **AVAILABLE DECORS**



#### ENDURO 3D foil



#### **ENDURO PLUS foil**





duro walnut eterno oak grey oak

#### **ECO-VENEER CPL**





#### CONSTRUCTION

- coating: finger joint pinewood
- 2 filling: fireproof chipboard
  - frame with filling is covered with HDF boards on both sides
  - door leaf covered with ENDURO foil or ECO-VENEER
- door leaf thickness: El, 30—50 mm / El, 60—60 mm
- rounded vertical edges of door leaves (more info on page 94)
- width of single doors: "70"-"100"
- width of double doors: "140"-"220"

#### STANDARD EQUIPMENT

- · cylinder lock + insert
- 4 hinges with regulation
- intumescent seals
- automatic bottom door seal

ATTENTION: automatic bottom door seal not applicable for doors with fixed threshold

#### **REQUIRED EQUIPMENT AT EXTRA CHARGE**

- self-closer
- cylinder lock
- UNO door handle
- closing sequence controller (double door)

ATTENTION: the seller's obligation is to sell technical doors equipped with the above elements

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

- viewfinder
- smoke protection
- set of 8 mounting screws with expansion sleeves in sizes 10/152 for brick walls

אומ	NENSIONS		single	e door		double door*									
Diiv	ILINGIONS	"70"	"80"	"90"**	"100"	"140"	"150"	"160"	"170"	"180"	"190"	"200"	"210"	"220"	
s1	door leaf width	748	848	964	1048	1487	1587	1687	1787	1887	1987	2087	2187	2287	
s2	width of wall opening	856	956	1072	1156	1595	1695	1795	1895	1995	2095	2195	2295	2395	
s3	outer width of door frame	826	926	1042	1126	1565	1665	1765	1865	1965	2065	2165	2265	2365	
s4	internal width of door frame	706	806	922	1006	1445	1545	1645	1745	1845	1945	2045	2145	2245	
h1	door leaf height		20	040				2		2040	2		2		
h2	internal height of door frame		2100			2100									
h3	outer height of door frame		2084							2084					
h4	internal height of door frame		2024				•		-	2024	-				

\*Internal width of door frame in case of double door 90+90 after opening the active door leaf at an angle of 90 ° is at least 900 mm, so the passive door leaf is narrower. The door set is asymmetric regarding widths of both door leaves. \*\*Internal width of door frame after opening the door leaf at an angle of 90° is at least 900 mm

#### **AVAILABLE DOOR FRAMES**



• **[KOBP]** block door frame 124 x 60 mm made of finger-jointpinewood

#### ADDITIONAL OPTIONS AT EXTRA CHARGE FOR BLOCK DOOR FRAME

- covering profile (architrave LO1)—"70"-"100"
- quadrant LC1-"70"-"100"
- enlarging element—100 mm, 200 mm, 300 mm


## **Dimensions**


#### **DIMENSIONS OF REBATED DOORS**

	"60"	"70"	"80"	"90"	"100"
Α	618	718	818	918	1018
В	644	744	844	944	1044
С		1)	PL) <b>2027 / 1975</b> (CZ-S	к)	
D		(1	PL) <b>2040 / 1988</b> (CZ-S	к)	

DIMENSIONS **A** AND **C** ARE OUTER DIMENSIONS OF **NON-REBATED DOORS**; DIMENSIONS **B** AND **D** ARE OUTER DIMENSIONS OF **REBATED DOORS** AND DOORS PREPARED FOR **SLIDING SYSTEMS** 

#### **Contact edges of double doors**





# Rounded vertical and upper edges in door leaves

DOORS	STA	ANDARD DOORS	SLIDING SYSTEMS	EDGE FROM THE CONTACT SIDE		
DOORS	REBATED	NON-REBATED	SLIDING STSIEMS	OF DOUBLE DOOR		
MODULAR DOORS	YES	YES	YES	YES		
FLAT DOORS	YES		NO	NO		
FOLDING DOORS	YES*					
EGIDA	YES					
GUARDIA	YES**			NO		
IGNIS	YES					

\*OUTER VERTICAL EDGES ONLY. \*\*ENDURO FOIL AND ECO-VENEER ONLY

## Ventilation

According to the norm, the door to the bathroom, shower and separate WC should open outwards, have the passage width of at least 0.8 m and height of 2 m, and have the ventilation holes for the air supply in the bottom of the door with total ventilation area of at least 0.022 m². The total ventilation area is the sum of the gap under the door (standard 7 mm) and additional solutions that increase the total net ventilation area such as: ventilation sleeves, ventilation undercut and ventilation grid. The use of ventilation grid ensures the correct ventilation area for all door widths, while using the sleeve and/or undercut the increased gap between the door and the floor should be used in order to meet the required regulations. If regulations mentioned above must be obliged, the clients must trim the door on their own.

#### GUIDELINES FOR BUILDINGS EQUIPPED WITH A RECUPERATION SYSTEM

To ensure adequate air flow from the living areas to the corridor, sanitary, and auxiliary rooms, it is recommended that all internal doors should have a gap at the bottom. The gap area in doors in living and auxiliary rooms should be at least 80 cm² (INVADO doors with an undercut fully meet this requirement). The size of the ventilation gap in doors in sanitary rooms should be 200 cm<sup>2</sup>.







ventilation grid (Norma Decor)









round or square ventilation sleeves

door width	number of ventilation sleeves	door leaf with metal ventilation sleeves total ventilation area: ventilation sleeves and the gap under the door (7 mm) [m2]	door leaf with PVC ventilation sleeves for foiled doors total ventilation area: ventilation sleeves and the gap under the door (7 mm)	door leaf with PVC ventilation sleeves for modular doors total ventilation area: ventilation sleeves and the gap under the door (7 mm) [m2]	total ventilation area: ventilation undercut and the gap under the door (7 mm) [m2]	total ventilation area: ventilation grid and the gap under the door (7 mm) [m2]
"60"	3	0.0069	0.0062	0.0056	0.00835	
"70"	4	0.0085	0.0075	0.0067	0.01085	
"80"	5	0.0101	0.0089	0.0079	0.01335	> 0.022
"90"	6	0.0117	0.0103	0.0090	0.01585	> 0.022
"100"	6	0.0124	0.0110	0.0097	0.01835	
"110"	6	0.0131	0.0117	0.0104	0.02085	

DOOR COLLECTIONS WHERE THE VENTILATION SLEEVES. VENTILATION UNDERCUT AND VENTILATION GRID CANNOT BE USED: D'ARTAGNAN COLLECTION.

THERE IS NO POSSIBILITY TO SIMULTANEOUSLY USE MORE SOLUTIONS FOR VENTILATION IN INVADO DOORS



# **Block door frame for rebated doors**













CAPS FOR HINGES

#### **CONSTRUCTION**


- MDF board
- foiling—all decors available in the INVADO offer
- cross-section: 90 x 44 mm

#### DOOR FRAME FOR DOOR LEAVES IN WIDTH


- width of single doors "60" to "100"
- width of double doors "120" to "200"

#### **OPTIONS AT EXTRA CHARGE FOR BLOCK DOOR FRAMES**

- flat architrave LO1 60 x 10 mm
- flat architrave LO7 80 x 16 mm
- auadrant LC1
- door frames with sidelights and transoms (without glass) with circumference up to  $5\,\mathrm{l.m}$
- · door frames for double doors
- additional hinge in door frame "60"-"80"



COVERING TRIMS (101) AND QUADRANT (1C1) CAN BE APPLIED TO A BLOCK DOOR FRAME FOR DOOR LEAVES IN WIDTHS "60"—"90". IN CASE OF DOOR LEAVES IN WIDTH "100" YOU HAVE TO ORDER DOUBLE COVERING TRIM OR DOUBLE QUADRANT (LC2).



	ENSIONS OF DOOR LEAF D DOOR FRAME		single door						double door							
		door leaf:	"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width		644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
s2	width of the wall opening		718	818	918	1018	1118	1338	1438	1538	1638	1738	1838	1938	2038	2138
s3	outer width of the door frame		688	788	888	988	1088	1308	1408	1508	1608	1708	1808	1908	2008	2108
s <b>4</b>	internal width of the door frame		600	700	800	900	1000	1220	1320	1420	1520	1620	1720	1820	1920	2020
h1	door leaf height			-		-	-	(F	<b>°L)</b> 2040 /	1987 <b>(cz-s</b>	SK)			-		
h2	height of the wall opening			•				(F	<b>L)</b> 2084 / 1	2029 <b>(cz-</b> s	SK)					
h3	outer height of the door frame		(PL) 2069 / 2014 (CZ-SK)													
h4	internal height of the door frame			(PL) 2025 / 1970 (Cz-sk)												

ORS1 / ORS8

# Adjustable door frame for rebated doors







**ADJUSTABLE DOOR FRAME INSTALLATION** 



#### CONSTRUCTION

- MDF board
- foiling—all decors available in the INVADO offer
- standard adjustable door frame consists of central element plus 2 sets of angle architraves joined at 45°. Standard angle architrave consists of a flat architrave 60 mm-wide and a "tongue" 30 mm-long. There is a possibility to order:

  - a) adjustable door frame with a flat angle architrave 80 mm-wide (ORS8), b) a set of flat angle architraves 80 mm-wide with a "tongue" 50 mm-long (sold separately). See the table of options at extra charge.

#### DOOR FRAME FOR DOOR LEAVES IN WIDTH


- width of single doors "60" to "100"
- · width of double doors "120" to "200"

#### **OPTIONS AT EXTRA CHARGE FOR ADJUSTABLE DOOR FRAMES**

- $\bullet\,$  door frames with sidelights and transoms (without glass) with circumference up to 5 l.m
- door frames for double doors
- additional hinge in door frame "60"-"80"
- standard angle architrave (a "tongue" 30 mm-long, an architrave 60 or 80 mm-wide)
- angle architrave with longer "tongue" (a "tongue" 50 mm-long, an architrave 60 or 80 mm-wide)
- wall framing ("blind door frame")

#### RANGES OF WALL THICKNESS COVERING

Adjustable door fame is made in dimensions adjustable to the wall thickness in steps of 20 mm. The minimum wall thickness is 75 mm. **NOTE: due to special mills there is a possibility to trim the frame and**  $\textbf{reduce the wall thickness coverage by 15 mm.} \ \mathsf{Door frame for the wall thickness} \ \mathsf{greater than} \ \mathsf{340} \ \mathsf{mm}$ consists of at least two connected components.





	ENSIONS OF DOOR L DOOR FRAME	EAF		si	ngle do	or					d	ouble do	oor			
		door leaf:	"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width		644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
s2	width of the wall opening		674	774	874	974	1074	1294	1394	1494	1594	1694	1794	1894	1994	2094
s3	outer width of the door fro	ame	644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
s <b>4</b>	internal width of the door	frame	600	700	800	900	1000	1220	1320	1420	1520	1620	1720	1820	1920	2020
_	width of the door frame	60 mm [ORS1]	744	844	944	1044	1144	1364	1464	1564	1664	1764	1864	1964	2064	2164
s5	with architraves	80 mm [ORS8]	784	884	984	1084	1184	1404	1504	1604	1704	1804	1904	2004	2104	2204
h1	door leaf height				•	-		(1	2040 /	1988 <b>(cz-s</b>	K)	•	-			-
h2	height of the wall opening	g			•			(1	<b>PL)</b> 2062 /	2008 (cz-s	K)					-
h3	outer height of the door f	rame			-			(1	PL) 2047 /	1993 <b>(cz-s</b>	K)					
h4	internal height of the doo	r frame						(1	<b>ะเ)</b> 2025 /	1971 <b>(cz-s</b>	К)					
	height of the door	60 mm [ORS1]		•	•			(1	<b>PL)</b> 2097 /	2043 <b>(cz-s</b>	к)		•	•		•
h5	frame with architraves	80 mm [ORS8]						(1	<b>21</b> 17 /	2063 <b>(cz-s</b>	K)					*

#### NOMINAL COVERAGE OF THE WALL FOR ADJUSTABLE DOOR FRAMES

symbol	Α	В	С	D	E	F	G	Н	I	J	
wall thickness	75–94	95–114	120–139	140–159	160–179	180–199	200–219	220–239	240–259	260–279	
symbol	K	L	M	N	0	P	Q	R	S	T	U
wall thickness	280–299	300–319	320–339	340–359	360–379	380–399	400–419	420–439	440–459	460–479	480–499*

\*It is possible to order adjustable door frame thicker than 499 mm—for this purpose please contact with INVADO's commercial department



#### Adjustable door frame for non-rebated modular doors **ORS7/ ORS10**







#### **CONSTRUCTION**

- MDF board
- foiling—all decors available in the INVADO offer
- standard adjustable door frame consists of central element plus 2 sets of angle architraves joined at 45°. Standard angle architrave consists of a flat architrave 60 mm-wide and a "tongue" 30 mm-long. There is a possibility to order:
  - a) adjustable door frame with a flat angle architrave 80 mm-wide (ORS10)
- b) a set of angle architraves 80 mm-wide with a "tongue" 50 mm-long (sold separately). See the table of options at extra charge

#### DOOR FRAME FOR DOOR LEAVES IN WIDTH


- width of single doors "60" to "100"
- · width of double doors "120" to "200"

#### **OPTIONS AT EXTRA CHARGE FOR ADJUSTABLE NON-REBATED MODULAR DOORS**

- door frames with sidelights and transoms (without glass) with circumference up to 5 l.m
- · door frames for double doors
- · additional hinge in door frame
- · standard angle architrave (a "tonque" 30 mm-long, an architrave 60 or 80 mm-wide)
- angle architrave with longer "tongue" (a "tongue" 50 mm-long, an architrave 60 or 80 mm-wide)

#### RANGES OF WALL THICKNESS COVERING

Adjustable door fame is made in dimensions adjustable to the wall thickness in steps of 20 mm. The minimum wall thickness is 75 mm. NOTE: due to special mills there is a possibility to trim the frame and reduce the wall thickness coverage by 15 mm. Door frame for the wall thickness greater than 340 mm consists of at least two connected components.



	ENSIONS OF DOOR L	EAF		si	ngle do	or					de	ouble do	oor			
		door leaf:	"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width		618	718	818	918	1018	1239	1339	1439	1539	1639	1739	1839	1939	2039
<b>s2</b>	width of the wall opening	-	674	774	874	974	1074	1294	1394	1494	1594	1694	1794	1894	1994	2094
s3	outer width of the door fro	ame	644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
s4	internal width of the door	frame	600	700	800	900	1000	1220	1320	1420	1520	1620	1720	1820	1920	2020
	width of the door frame	60 mm [ORS7]	744	844	944	1044	1144	1364	1464	1564	1664	1764	1864	1964	2064	2164
<b>s</b> 5	with architraves	80 mm [ORS10]	784	884	984	1084	1184	1404	1504	1604	1704	1804	1904	2004	2104	2204
h1	door leaf height			•				(1	PL) 2027 /	1975 <b>(cz-s</b>	iK)		*			
h2	height of the wall opening	9		•				(1	PL) 2062 /	2008 <b>(cz-s</b>	iK)					
h3	outer height of the door fr	rame						(1	PL) 2047 /	1993 <b>(cz-s</b>	iK)					-
h4	internal height of the doo	r frame			-			(1	PL) 2025 /	1971 <b>(cz-s</b>	K)					
h5	height of the door	60 mm [ORS7]						(1	PL) 2097 /	2043 <b>(cz-s</b>	iK)		•			
n5	frame with architraves	80 mm [ORS10]						(1	PL) 2117 /	2063 <b>(cz-s</b>	iK)				-	

#### NOMINAL COVERAGE OF THE WALL FOR ADJUSTABLE DOOR FRAMES

symbol	A	В	С	D	E	F	G	Н	ı	J	
wall thickness	75–94	95–114	120–139	140–159	160–179	180–199	200–219	220–239	240–259	260–279	
symbol	K	L	М	N	0	P	Q	R	S	Т	U
wall thickness	280–299	300–319	320–339	340–359	360–379	380–399	400–419	420–439	440–459	460–479	480–499*

\*It is possible to order adjustable door frame thicker than 499 mm—for this purpose please contact with INVADO's commercial department

#### FD 11 / FD 12

# **Metal door frame (big)**



#### **CONSTRUCTION**

- · welded frame
- ungalvanized plate with a thickness of 1.2 mm
- powder-coated frame in a choice of standard RAL colours
- 2 hinges in color white zinc and a seal included
- universal mounting brackets for brick walls and plasterboard walls


#### DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "110"
- width of double doors "120" to "200"

#### RANGES OF WALL THICKNESS COVERING

- door frame **FD11**—75 mm
- door frame FD12—100 mm

DIM	ENSIONS OF DOOR LEAF		si	ngle do	or	_	double door								
ANI	DOOR FRAME FD11 AND FD12	"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
s2	width of the wall opening	670	770	870	970	1070	1290	1390	1490	1590	1690	1790	1890	1990	2090
s3	outer width of the door frame	696	796	896	996	1096	1316	1416	1516	1616	1716	1816	1916	2016	2116
s4	internal width of the door frame	600	700	800	900	1000	1220	1320	1420	1520	1620	1720	1820	1920	2020
h1	door leaf height							•	2040	•	•	-	•	•	
h2	height of the wall opening								2037						
h3	outer height of the door frame				•				2072	•		***************************************			
h4	internal height of the door frame							•	2024	•	•		-	•	
	•	±	•	•	•	•		•	•	•	•	•	•	•	



#### **OPTIONS AT EXTRA CHARGE FOR METAL DOOR FRAMES**


- reinforcement for the self-closer
- adapted for electric door strike


AVAILABLE DECORS RAL: 9010—white / 9016—white / 8017—chocolate brown / 7047—gray / 7024—graphite / 1001—beige



# Metal door frame (small)







#### **CONSTRUCTION**

- · welded frame
- ungalvanized plate with a thickness of 1.2 mm
- powder-coated frame in a choice of standard RAL colours
- 2 hinges in white zinc and seal included
- universal mounting brackets for brick walls and plasterboard walls

#### DOOR FRAME FOR DOOR LEAVES IN WIDTH


- width of single doors "60" to "110"
- width of double doors "120" to "200"


DIM	ENSIONS OF DOOR LEAF		si	ngle do	or					d	ouble do	or			
AND	DOOR FRAME FD14	"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
s2	width of the wall opening	661	761	861	961	1061	1281	1381	1481	1581	1681	1781	1881	1981	2081
s3	outer width of the door frame	696	796	896	996	1096	1316	1416	1516	1616	1716	1816	1916	2016	2116
s4	internal width of the door frame	600	700	800	900	1000	1220	1320	1420	1520	1620	1720	1820	1920	2020
h1	door leaf height					-			2040						
h2	height of the wall opening							•	2038		-			-	
h3	outer height of the door frame		-	-		-		-	2072					-	
h4	internal height of the door frame							•	2024			•	•	***************************************	***************************************

## FD 61-67

# Adjustable metal door frame







#### CONSTRUCTION

- 2-part frame, adjustable (adjustment range in 30 mm steps)
- · ungalvanized plate with a thickness of 1.5 mm
- powder-coated frame in a choice of standard RAL colours
- 3 hinges in color white zinc and seal included
- universal mounting brackets for brick walls and plasterboard walls

#### DOOR FRAME FOR DOOR LEAVES IN WIDTH


- width of single doors "60" to "110"
- width of double doors "120" to "200"

RANGES	OF WAL	L THICKNESS	COVERING
	<b>-</b>		

door frame:	FD61	FD62	FD63	FD64	FD65	FD66	FD67
ranges:	95–125	125–155	155–185	185–215	215–245	245–275	275–305

	ENSIONS OF DOOR LEAF DOOR FRAME		si	ngle do	or	-				d	ouble do	or			
ADJ	USTABLE METAL DOOR FRAME	"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
s2	width of the wall opening	683	783	883	983	1083	1300	1400	1500	1600	1700	1800	1900	2000	2100
s3	outer width of the door frame	716	816	916	1016	1116	1334	1434	1534	1634	1734	1834	1934	2340	2134
s4	internal width of the door frame	600	700	800	900	1000	1220	1320	1420	1520	1620	1720	1820	1920	2020
h1	door leaf height		<b>L</b>	<u>-</u>	•	*		•	2040	-	-	•	•	•	•
h2	height of the wall opening								2065						
h3	outer height of the door frame			-					2082			-		•	-
h4	internal height of the door frame	2024													

# **Concealed door frame SARA-PRO**



NON-REBATED DOOR LEAF FOR OUTER DOOR FRAME AND REBATED DOOR LEAF FOR INNER DOOR FRAME BASED ON DOOR LEAF NORMA DECOR 1 The SARA-PRO door frame introduces a completely new quality in interior decoration. Invisible to the naked eye, it makes the area lighter. Ideal for minimalist and modern interiors. Available in outer and inner version.

no extra charae

#### CONSTRUCTION

- the frame is made of MDF board
- the surface and edges of a door leaf are primed and prepared for painting or wallpapering (painting and wallpapering on your own)
- filling—"honeycomb"
- frame with filling is covered with HDF boards on both sides
- width of single doors "60"-"90"

#### STANDARD EQUIPMENT OF A DOOR LEAF

- · 2 hidden hinges
- magnetic lock for standard key, WC knob or cylinder lock insert

#### ADDITIONAL OPTIONS AT EXTRA CHARGE

door without a key hole


ooi wiirioora key riole

- ventilation undercut
- PVC ventilation sleeves
- cylinder lock insert 31/36
- filling—tubular chipboard
- automatic door bottom seal for door width "60"-"90"
- ventilation grid


#### DIMENSIONS OF A DOOR LEAF AND CONCEALED DOOR FRAME

			inner do	or frame	•		outer do	or frame	•
	size	"60"	"70"	"80"	"90"	"60"	"70"	"80"	"90"
s1	door leaf width	618	718	818	918	618	718	818	918
s2	width of the wall opening	698	798	898	998	698	798	818	918
s3	outer width of the door frame	688	788	888	988	688	788	898	998
s4	internal width of the door frame	603	703	803	903	603	703	888	988
h1	door leaf height			)1 <i>7</i>				)1 <i>7</i>	
h2	height of the wall opening			76			20	)66	
h3	outer height of the door frame			69	•			)59	
h4	internal height of the door frame		20	)27			20	)17	

#### CONCEALED DOOR FRAME SARA-PRO—INNER




#### CONCEALED DOOR FRAME SARA-PRO—OUTER





# **Housing system for metal frames**






#### **FEATURES**

Metal frame housing (covering) allows to install new doors in the rooms where metal frames were mounted in accordance with the Polish standard (regarding dimensions) without having to remove these frames. The advantage of this solution is an easy installation with mounting foam, without dirty floors and walls, and the ability to mount a standard foiled INVADO door leaves.

WIDTH OF THE DOOR FRAME FOR DOOR LEAVES	INTE	RNAL DIMENSIONS OF ME	TAL DOOR FRAM	E (mm)		
width of single doors"60" to "100"	door	leaf:	"60"	"70"	"80"	"90"
RANGES OF WALL THICKNESS	s1	door leaf width	600	700	800	900
• 60–94, 95–129, 130–199, 200–269	h1	door leaf height		(PL) 2025 /	1975 (CZ/SK)	



# Foiled and modular doors



caps for hinges (satinated chrome, chrome, black or golden)



hinge



**hidden hinge** (non-rebated doors)



cylinder lock insert



automatic bottom door seal



porthole (black or silver with satinated or transparent glass)



aluminum threshold



ventilation sleeves—round



ventilation sleeves—square



ventilation grid




door seal (package 5.5 m) colours: BLACK /WHITE / GRAY / BROWN / BEIGE

# **KICK and PUSH metal panels**

#### **INFORMATIONS:**

- material: polished stainless steel;
- dimensions: width matched to the door leaf, height 300 mm, thickness 0.6 mm;
- ventilation undercut—height: 15 mm;
- $\bullet \ \ \text{ventilation sleeves} \\ -\text{diameter: 40 mm (depending on the width of the door leaf, a different number of the door leaf)} \\$  $ventilation\ sleeves\ are\ used:\ "60"-3\ sleeves\ /\ "70"-4\ sleeves\ /\ "80"-5\ sleeves\ /\ "90"-"100"-6\ sleeves;$
- ventilation grid—dimensions: 430 x 110 mm.



KICK bottom panel with ventilation grid





# **Sliding systems**



key hook lock WC \ KEY



grip with folding key and a thimble



grip with WC knob and a thimble



grip and a thimble



strike plate



soft-close hardware for sliding door



door seal (pocket door sliding system)



profiles and architraves (pocket door sliding system)



brush (pocket door sliding system)



bumper (wall-mounted sliding system)



rail cover (wall-mounted sliding system)

# **Technical doors**



cylinder lock insert (Guardia / Ignis)



cylinder lock insert with a WILKA knob (Egida)



automatic bottom door seal (Guardia / Egida)



panoramic viewfinder (Guardia / Egida)



self-closer (Guardia / Ignis)



intumescent seals (Guardia)



cylinder (Guardia)




hinge with regulation (Guardia)





handle QUEBECK (TYTAN / INOX) / ROYAL (INOX) (Egida)

# **Glass doors**

















black









































glossy chrome













glossy chrome

matt chrome













nickel/chrome



























no Escutcheon









handle **UNO** 







stainless steel

SKIRTINGS COLLECTION
PESTIGE

WATCH ON OUR YOUTUBE CHANNEL
PRESTIGE
SKIRTINGS
INSTALLATION

















#### ADDITIONAL OPTIONS AT EXTRA CHARGE

- finishing element 20 x 20 x 120 mm
- clips—30 pcs/package

Skirting length—240 cm. Skirtings are packed 5 pcs/package. The price is for 1 piece



















### ARBONIA & Group

All information in the catalogue do not constitute an offer within the meaning of the Civil Code and are published for informational purposes only. Manufacturer reserves the right to make changes.

Note! Due to the printing technique the colors of the products presented in the catalogue may differ from the original. All rights reserved. Copying and publication of this catalogue on web sites and in other media without the written consent from INVADO Sp. z o.o. is prohibited.

Distributor's stamp: